

Serial No.: 10/728,617
Examiner: E. Kcaney
Title: LIGHT-EMITTING UNIT AND ILLUMINATOR UTILIZING THE SAME

Amendments to the Claims:

1. (currently amended) A light-emitting unit comprising:

a substrate including an obverse surface and a reverse surface;
a first light-emitting element mounted on the obverse surface of the substrate, and
a second light-emitting element mounted on the reverse surface of the substrate;
a first lens arranged for dispersion of light and enclosing the first light-emitting
element, and a second lens arranged for dispersion of light and enclosing the second
light-emitting element; ~~and~~

a first wiring pattern formed on the obverse surface of the substrate, and a second
wiring pattern formed on the reverse surface of the substrate; and

a reflecting layer arranged between each lens and a corresponding one of the first
and second wiring patterns;

wherein each lens includes a periphery which is adjacent to at least a part of an
edge of the substrate; and

wherein the reflecting layer is formed with an opening in which said
corresponding one of the first and second wiring patterns is partially exposed.

2. (original) The unit according to claim 1, wherein the periphery of each lens is circular,
the edge of the substrate including an arcuate portion extending along the circular
periphery of said each lens.

3. (original) The unit according to claim 1, wherein the dispersion of light for each lens is
provided by causing said each lens to contain light-dispersing particles.

4. (currently amended) The unit according to claim 1, ~~further comprising a reflecting
layer arranged between each lens and the substrate, wherein the reflecting layer is formed
with an opening in which the substrate is partially exposed, and~~ wherein the substrate is
made of a transparent material.

Serial No.: 10/728,617
Examiner: E. Kcancy
Title: LIGHT-EMITTING UNIT AND ILLUMINATOR UTILIZING THE SAME

5. (original) The unit according to claim 1, wherein the substrate has a rectangular configuration including a first end and a second end which are spaced apart from each other, the first end being provided with a first terminal, the second end being provided with a second terminal, and wherein each light-emitting element and each lens are disposed in a central region of the substrate between the first terminal and the second terminal.
6. (original) The unit according to claim 1, further comprising an additional light-emitting element mounted on the obverse surface of the substrate and enclosed by the first lens, wherein the first light-emitting element and the additional light-emitting element are energized through different current paths independent of each other.
7. (original) The unit according to claim 6, wherein the first light-emitting element and the additional light-emitting element are connected with opposite polarities.
8. (currently amended) The unit according to claim 1, further comprising a black layer covering ~~at least~~ only a part of the substrate ~~between~~ around the periphery of the lens ~~and along~~ the edge of the substrate.
9. (original) The unit according to claim 1, wherein each light-emitting element includes a supporting base, a light-emitting diode chip mounted on the base, and a transparent resin member enclosing the chip.
10. (original) The unit according to claim 9, wherein the base has an elongated rectangular configuration and a center line that extends longitudinally of the base, the center line passing through a center of the lens.
11. (original) The unit according to claim 1, wherein each light-emitting element includes a light-emitting diode chip diebonded to a corresponding one of the wiring patterns, and a metal wire connected to the chip.

Serial No.: 10/728,617

Examiner: E. Keaney

Title: LIGHT-EMITTING UNIT AND ILLUMINATOR UTILIZING THE SAME

12. (original) The unit according to claim 11, wherein the metal wire is arranged to extend along a straight line passing through a center of the lens.

13. (original) An illuminator comprising:

- a substrate including an obverse surface and a reverse surface;

- a first light-emitting element mounted on the obverse surface of the substrate, and a second light-emitting element mounted on the reverse surface of the substrate;

- a first lens arranged for dispersion of light and enclosing the first light-emitting element, and a second lens arranged for dispersion of light and enclosing the second light-emitting element;

- a first wiring pattern formed on the obverse surface of the substrate, and a second wiring pattern formed on the reverse surface of the substrate;

- a base connected to the wiring patterns; and

- an envelope for accommodating the substrate, the light-emitting elements, the lenses and the wiring patterns;

- wherein each lens includes a periphery which is adjacent to at least a part of an edge of the substrate.

14. (original) The illuminator according to claim 13, wherein the periphery of each lens is circular, the edge of the substrate including an arcuate portion extending along the circular periphery of said each lens.

15. (original) The illuminator according to claim 13, further comprising an additional light-emitting element mounted on the obverse surface of the substrate and enclosed by the first lens, wherein the first light-emitting element and the additional light-emitting element are energized through different current paths independent of each other.

16. (original) The illuminator according to claim 15, wherein the first light-emitting element and the additional light-emitting element are connected with opposite polarities.

Serial No.: 10728.617
Examiner: E. Keaney
Title: LIGHT-EMITTING UNIT AND ILLUMINATOR UTILIZING THE SAME

17. (original) The illuminator according to claim 13, further comprising a black layer covering at least part of the substrate between the periphery of the lens and the edge of the substrate.

18. (original) The illuminator according to claim 13, wherein each light-emitting element includes a supporting base, a light-emitting diode chip mounted on the supporting base, and a transparent resin member enclosing the chip.

19. (original) The illuminator according to claim 18, wherein the supporting base has an elongated rectangular configuration and a center line that extends longitudinally of the supporting base, the center line passing through a center of the lens.

20. (original) The illuminator according to claim 13, wherein each light-emitting element includes a light-emitting diode chip diebonded to a corresponding one of the wiring patterns, and a metal wire connected to the chip.

21. (new) A light-emitting unit comprising:

- a substrate including an obverse surface and a reverse surface;

- a first light-emitting element mounted on the obverse surface of the substrate, and a second light-emitting element mounted on the reverse surface of the substrate;

- a first lens arranged for dispersion of light and enclosing the first light-emitting element, and a second lens arranged for dispersion of light and enclosing the second light-emitting element; and

- a first wiring pattern formed on the obverse surface of the substrate, and a second wiring pattern formed on the reverse surface of the substrate;

- wherein each lens includes a periphery which is adjacent to at least a part of an edge of the substrate;

- wherein the light-emitting unit further comprises an additional light-emitting element mounted on the obverse surface of the substrate and enclosed by the first lens; and

Serial No.: 10728,617
Examiner: E. Keaney
Title: LIGHT-EMITTING UNIT AND ILLUMINATOR UTILIZING THE SAME

wherein the first light-emitting element and the additional light-emitting element are energized through different current paths independent of each other.

22. (new) the unit according to claim 21, wherein the first light-emitting element and the additional light-emitting element are connected with opposite polarities.